



QUIETMASTER® HEAVY DUTY ROOM AIR CONDITIONERS

SPECIFICATIONS / PERFORMANCE DATA

Model	Cooling Capacity BTU/h	Electrical Characteristics			Energy Efficiency Ratio EER	Moisture Removal Pts/h	Room Side Air Circulation CFM	Air Direction Controls
		Volts	Amps	Watts				
SL24J30A	24500/24500	230/208	11.9/13.0	2579/2606	9.5/9.4	7.7	560	8-way
SL28J30A	28000/27500	230/208	14.0/15.5	3111/3090	9.0/8.9	8.8	600	8-way
SL33J30	33000/32500	230/208	17.0/18.0	3667/3611	9.0/9.0	11.0	700	8-way

DIMENSIONS / WEIGHT / INSTALLATION INFORMATION

Model	Dimensions (inches)			Window Width (inches)		Thru-The-Wall Finished Hole (inches)		Circuit Breaker or T-D Fuse	Weight Lbs.	
	Height	Width	Depth	Min.	Max.	Height	Width		Net	Shipping
SL24J30A	20-3/16	28	33-5/8	29-7/8	42	20-3/8	28-1/4	250V-20A	192	212
SL28J30A	20-3/16	28	33-5/8	29-7/8	42	20-3/8	28-1/4	250V-20A	201	221
SL33J30	20-3/16	28	33-5/8	29-7/8	42	20-3/8	28-1/4	250V-30A	216	236

Due to continuing engineering research in new energy-saving technology, specifications are subject to change without notice.

These Friedrich models include accessories for window or thru-wall installation.

