

TEST SUBMISSION FORM

Date	02/24/2024	Sample Identification:	V81440		
Company	Veratex, Inc.	Lot: 18343/304482			
Address	P.O. Box 682 New York, NY 10108	Special Instructions: ASTM 6413			
Contact	Claude Simon				
Phone	912 441 0062	<input type="checkbox"/> Return Tested Specimens	<input checked="" type="checkbox"/> Please mark fabric face		
Email	csimon@fairlane.biz	<input type="checkbox"/> Return Extra Yardage	<input checked="" type="checkbox"/> Please email/call if not represented		
ABRASION		PILLING		GENERAL	
<input type="checkbox"/> Taber Method ASTM D3884 Weight: Wheels: _____ Cycles: _____		<input type="checkbox"/> Brush Pill ASTM D3511 <input type="checkbox"/> Martindale Pill ASTM D4970		<input type="checkbox"/> Count <input type="checkbox"/> Thickness ASTM D1777	
<input type="checkbox"/> Print Retention ASTM D3389		<input type="checkbox"/> Martindale Pill ISO 12945-2		<input type="checkbox"/> Stiffness (Circular Bend) ASTM D 4032	
<input type="checkbox"/> Martindale Method ASTM D4966 Cycles: _____		<input type="checkbox"/> Random Tumble ASTM D3512 <input type="checkbox"/> 30 min <input type="checkbox"/> 60 min		<input type="checkbox"/> Stiffness (Cantilever) ASTM D 1388 <input type="checkbox"/> Weight ASTM D 3776	
STRENGTH					
<input type="checkbox"/> Wyzenbeek Method ASTM D4157 Cycles: <input type="checkbox"/> CD <input type="checkbox"/> WS <input type="checkbox"/> Joint Ind.		<input type="checkbox"/> Break: Grab Method D5034 <input type="checkbox"/> Break: Fabric Strip Method D5035		<input type="checkbox"/> Width ASTM D 3774 <input type="checkbox"/> pH AATCC 81	
<input type="checkbox"/> Stoll Method: Flex ASTM D3885		<input type="checkbox"/> Tongue Tear ASTM D2261		<input type="checkbox"/> Water Repellency AATCC 70	
<input type="checkbox"/> Stoll Method: Inflated Diaphragm ASTM D3886 Cycles: _____ Abradant: _____		<input type="checkbox"/> Trapezoid Tear <input type="checkbox"/> ASTM D5587 <input type="checkbox"/> ASTMD D5733 <input type="checkbox"/> Elmendorf ASTM D1424		<input type="checkbox"/> Spray Rating AATCC 22 <input type="checkbox"/> Hydrostatic AATCC 127	
COLORFASTNESS					
Crocking AATCC: <input type="checkbox"/> 8 <input type="checkbox"/> 116		<input type="checkbox"/> Ball Burst ASTM D3787 <input type="checkbox"/> Mullen Burst ASTM D3786		<input type="checkbox"/> Hydrostatic ASTM D751 <input type="checkbox"/> Water/Alcohol Repellency AATCC 193	
<input type="checkbox"/> Dry Cleaning AATCC 132		<input type="checkbox"/> Seam Strength ASTM D1683		<input type="checkbox"/> Oil Repellency AATCC 118	
<input type="checkbox"/> Heat AATCC 117 Temp: _____		<input type="checkbox"/> Single Strand Yarn Strength ASTM D2256		<input type="checkbox"/> Wrinkle Recovery AATCC 128	
<input type="checkbox"/> Hot Pressing AATCC 133		<input type="checkbox"/> Elongation (with Breaking Load) ASTM D5034/D5035		<input type="checkbox"/> Shade Box AATCC 148	
<input type="checkbox"/> Light – Xenon AATCC 16.3 Hours: _____		Elongation Joint Ind. Ch. 10 <input type="checkbox"/> Woven <input type="checkbox"/> Knit		<input type="checkbox"/> Air Permeability ASTM D737	
Perspiration AATCC 15 <input type="checkbox"/> Acid <input type="checkbox"/> Alkaline <input type="checkbox"/> Both		Dynamic Seam Fatigue: <input type="checkbox"/> Joint Ind. Ch.22 <input type="checkbox"/> ASTM D4033 <input type="checkbox"/> DTL-101		<input type="checkbox"/> Wicking AATCC 197 <input type="checkbox"/> Fiber Migration JI Chapter 27	
<input type="checkbox"/> Solvent AATCC 107 modified		Yarn Slippage ASTM <input type="checkbox"/> D4034 <input type="checkbox"/> D434		<input type="checkbox"/> Spray Impact AATCC 42	
<input type="checkbox"/> Water AATCC 107		Stretch & Growth <input type="checkbox"/> ASTM D2594 <input type="checkbox"/> ASTM D3107 <input type="checkbox"/> ASTM D6614		<input type="checkbox"/> Hydrolysis ISO 1419 Weeks: _____	
Dye Transfer in Storage AATCC 163 <input type="checkbox"/> Option I <input type="checkbox"/> Option II		<input type="checkbox"/> SAE J855 Stretch & Set (Textiles and Plastics)		Snagging <input type="checkbox"/> ASTM D3939 Mace Method <input type="checkbox"/> ASTM D5362 Bean Bag Method	
Laundering AATCC 61 <input type="checkbox"/> 1A <input type="checkbox"/> 2A <input type="checkbox"/> 3A <input type="checkbox"/> 4A <input type="checkbox"/> 5A				<input type="checkbox"/> Flex Testing ASTM D2097	
<input type="checkbox"/> Chlorinated Pool AATCC 162		ANSI/AAMI PB70 Testing			
<input type="checkbox"/> Sea Water AATCC 106		<input type="checkbox"/> Level 1 – AATCC 42 Spray Impact			
<input type="checkbox"/> Water Spotting AATCC 104		<input type="checkbox"/> Level 2 – Spray Impact AATCC 42 & Hydrostatic AATCC 127			
Frosting AATCC <input type="checkbox"/> 119 <input type="checkbox"/> 120		<input type="checkbox"/> Level 3 – Spray Impact AATCC 42 & Hydrostatic AATCC 127			
<input type="checkbox"/> Weathering AATCC 169 Hours:					
<input type="checkbox"/> Phenolic Yellowing					

**** Unless otherwise specified, all compliance statements are simple acceptance.**

FLAMMABILITY	
UPHOLSTERY	APPAREL
British Standard	<input type="checkbox"/> Flammability of Wearing Apparel NFPA 702
<input type="checkbox"/> BS 5852 – Source: <input type="checkbox"/> 0 <input type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3 <input type="checkbox"/> 4 <input type="checkbox"/> 5	<input type="checkbox"/> Flammability of Apparel Textiles ASTM D-1230
<input type="checkbox"/> BS 7176 – Source: <input type="checkbox"/> 0 <input type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3 <input type="checkbox"/> 4 <input type="checkbox"/> 5	<input type="checkbox"/> Flammability of Clothing Textiles 16 CFR PART 1610
<input type="checkbox"/> BS EN 1021-1 <input type="checkbox"/> BS EN 1021-2	Children's Sleepwear 16 CFR 1615/1616 <input type="checkbox"/> Fabric <input type="checkbox"/> Garment
<input type="checkbox"/> California Technical Bulletin #117 <input type="checkbox"/> Cover Fabric <input type="checkbox"/> Barrier <input type="checkbox"/> Filling <input type="checkbox"/> Decking	ADDITIONAL FR TEST
<input type="checkbox"/> UFAC <input type="checkbox"/> NFPA 260 <input type="checkbox"/> Fabric Classification <input type="checkbox"/> Welt Cord <input type="checkbox"/> Barrier <input type="checkbox"/> Decking Materials <input type="checkbox"/> Decking Materials <input type="checkbox"/> Interior Fabrics <input type="checkbox"/> Decorative Trim <input type="checkbox"/> Filling / Padding Component	<input type="checkbox"/> CAN / ULC S109-14 Small Scale * CAN / ULC S109-14 Large Scale * <input type="checkbox"/> Folds <input type="checkbox"/> Flat * Test method requires both small and large scale testing
<input type="checkbox"/> Business & Institutional Furniture Manufacturer's Assoc.	California Title 19 Section 1237 <input type="checkbox"/> Indoor <input type="checkbox"/> Outdoor (includes original, leaching, and weathering)
<input type="checkbox"/> California Technical Bulletin #116	<input type="checkbox"/> Boston Fire Dept. BFD 1X-1
International Maritime Organization 652 (16) <input type="checkbox"/> Section 8.2 – Cigarette <input type="checkbox"/> Section 8.3 – Butane Flame	<input type="checkbox"/> New York Bulletin No. 44
<input type="checkbox"/> International Maritime Organization Part 8	<input type="checkbox"/> NY/NJ Port Authority
<input type="checkbox"/> CAN/CGSB 4.2 NO. 27.5 Flame Resistance 45° Angle Textile Flammability Regulation SOR/2016-194	<input type="checkbox"/> ASTM 6413 XXXXXXXX <input type="checkbox"/> FTMS-191-5903
<input type="checkbox"/> International Maritime Organization Part 7	<input type="checkbox"/> Federal Aviation Administration FAR 23.853/25.653 (Horizontal)
<input type="checkbox"/> NFPA 701-19 Test 1	<input type="checkbox"/> Federal Aviation Administration FAR 23.853/25.853 (Vertical) <input type="checkbox"/> 12 seconds <input type="checkbox"/> 60 seconds
NFPA 701-19 Test 2 <input type="checkbox"/> Fold <input type="checkbox"/> Flat	<input type="checkbox"/> Carpets & Rugs 16 CFR 1630/1631
<input type="checkbox"/> California Title 19 Section 1237 (Indoor)	<input type="checkbox"/> Sleeping Bags CPAI-75
<input type="checkbox"/> NFPA 705	<input type="checkbox"/> Tents CPAI-84 <input type="checkbox"/> Wall / Top <input type="checkbox"/> Flooring <input type="checkbox"/> Original Only <input type="checkbox"/> Complete Testing
British Standard	
BS 5867 Part 2 <input type="checkbox"/> Type B <input type="checkbox"/> Type C	
MATTRESS	
<input type="checkbox"/> International Maritime Organization Part 9	
16 CFR 1632 <input type="checkbox"/> Mattress <input type="checkbox"/> Mattress Pad <input type="checkbox"/> Mattress Ticking	
British Standard	
<input type="checkbox"/> BS EN 597-1 <input type="checkbox"/> BS EN 597-2	
<input type="checkbox"/> BS 7177 – Source: <input type="checkbox"/> 0 <input type="checkbox"/> 1 <input type="checkbox"/> 5	

**** Unless otherwise specified, all compliance statements are simple acceptance.**



LAUNDRY / DRY CLEANING / SOAKING

<input type="checkbox"/> Dimensional Change <input type="checkbox"/> Dimensional Stability <input type="checkbox"/> Commercial <input type="checkbox"/> Home <input type="checkbox"/> Dry Cleaning Cycles: _____ Check after _____ cycles. Wash Temp: <input type="checkbox"/> 80 <input type="checkbox"/> 105 <input type="checkbox"/> 120 <input type="checkbox"/> 140 <input type="checkbox"/> 160 <input type="checkbox"/> Other Drying: <input type="checkbox"/> Tumble-Low <input type="checkbox"/> Tumble-Dry <input type="checkbox"/> Drip <input type="checkbox"/> Line Evaluations: <input type="checkbox"/> Appearance <input type="checkbox"/> Pilling <input type="checkbox"/> Color <input type="checkbox"/> Snagging	ACT Test Method 1-2020 <input type="checkbox"/> BIFMA HFC 8.1 Available Cleaners: <input type="checkbox"/> 409 <input type="checkbox"/> Isopropyl Alcohol <input type="checkbox"/> Cavicide <input type="checkbox"/> Rescue <input type="checkbox"/> Virex Tb <input type="checkbox"/> Oxivir Five 16 <input type="checkbox"/> Ecolab QC A-456 II <input type="checkbox"/> Virex Plus <input type="checkbox"/> Perisept 62 <input type="checkbox"/> Virex II 256 <input type="checkbox"/> Lysol Disinfectant <input type="checkbox"/> Sanicloth Germicidal Disposable Wipes <input type="checkbox"/> Hydrogen Peroxide <input type="checkbox"/> 4:1 Water:Bleach <input type="checkbox"/> 10:1 Water:Bleach <input type="checkbox"/> Clorox Cleaner with Bleach <input type="checkbox"/> Other: _____
Soil Repellency <input type="checkbox"/> AATCC 130 <input type="checkbox"/> Tide <input type="checkbox"/> Ivory Snow <input type="checkbox"/> ASTM D1308	
Staining Agents: <input type="checkbox"/> Red Wine <input type="checkbox"/> Coffee <input type="checkbox"/> Grape Juice <input type="checkbox"/> Orange Juice <input type="checkbox"/> Beer <input type="checkbox"/> Tea <input type="checkbox"/> Milk <input type="checkbox"/> Cola <input type="checkbox"/> Whiskey <input type="checkbox"/> Kool-Aid <input type="checkbox"/> Ketchup <input type="checkbox"/> Mustard <input type="checkbox"/> Chocolate Syrup <input type="checkbox"/> Jelly <input type="checkbox"/> Salsa <input type="checkbox"/> Mayonnaise <input type="checkbox"/> Ice Cream <input type="checkbox"/> Grease <input type="checkbox"/> Dirt/Mud <input type="checkbox"/> Pen <input type="checkbox"/> Crayon <input type="checkbox"/> Salad Dressing <input type="checkbox"/> Washable Magic Marker <input type="checkbox"/> Liquid Ink <input type="checkbox"/> Vegetable Oil <input type="checkbox"/> Permanent Marker <input type="checkbox"/> Blood <input type="checkbox"/> Lipstick <input type="checkbox"/> Iodine <input type="checkbox"/> Betadine <input type="checkbox"/> Urine <input type="checkbox"/> Motor Oil <input type="checkbox"/> Suntan Lotion <input type="checkbox"/> Shoe Polish <input type="checkbox"/> Other: _____	
ASTM D3597 <input type="checkbox"/> Water <input type="checkbox"/> Solvent	
** Unless otherwise specified, all compliance statements are simple acceptance.	

Effective Date: 3/8/2023